

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	06819
NAME:	<i>tert</i> -Butyl acetate
SYNONYMS:	1,1-Dimethylethyl ester Acetic acid <i>tert</i> -butyl ester
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
FLAMMABLE LIQUIDS (CATEGORY 2), H225

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)
H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR.

PRECAUTIONARY STATEMENT(S)

P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

P233 KEEP CONTAINER TIGHTLY CLOSED.

P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.

P241 USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/ LIGHTING/ EQUIPMENT.

P242 USE ONLY NON-SPARKING TOOLS.

P243 TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.

P280 WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE PROTECTION.

P303 + P361 + P353 IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER.

P370 + P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM FOR EXTINCTION.

P403 + P235 STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: C₆H₁₂O₂

MW: 116.16

CAS-NO. 540-88-5

PURITY: 99 - 100% (GC)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
<i>tert</i> -Butyl acetate		

	FLAM. LIQ. 2; H225	<= 100 %
--	--------------------	----------

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	FLUSH EYES WITH WATER AS A PRECAUTION.
IF SWALLOWED	DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY CHEMICAL OR CARBON DIOXIDE.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	CARBON OXIDES

ADVICE FOR FIREFIGHTERS	WEAR SELF-CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.
FURTHER INFORMATION	USE WATER SPRAY TO COOL UNOPENED CONTAINERS.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	USE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN ACCUMULATE IN LOW AREAS. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS	PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET-BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS (SEE SECTION 13).
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	AVOID INHALATION OF VAPOUR OR MIST. USE EXPLOSION-PROOF EQUIPMENT.KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE. FOR PRECAUTIONS SEE SECTION 2.2.
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. STORAGE CLASS (TRGS 510): FLAMMABLE LIQUIDS
SPECIFIC END USE(S)	APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
tert-Butyl acetate	540-88-5	TWA	200 PPM	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
	REMARKS	UPPER RESPIRATORY TRACT IRRITATION EYE IRRITATION		
		TWA	200.000000 PPM	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		UPPER RESPIRATORY TRACT IRRITATION EYE IRRITATION		
		TWA	200.000000 PPM 950.000000 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		THE VALUE IN MG/M3 IS APPROXIMATE.		
		TWA	200.000000 PPM 950.000000 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICE. WASH HANDS BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.4 MM

BREAK THROUGH TIME: 30 MIN

MATERIAL TESTED: CAMATRIL (KCL 730, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

IMPERVIOUS CLOTHING, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear, Free or clear colorless liquid
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING POINT/FREEZING POINT	
INITIAL BOILING POINT AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	LOWER EXPLOSION LIMIT: 1.5 - 1.7 %(V)
VAPOUR PRESSURE	56 HPA (42 MMHG) AT 20 C
VAPOUR DENSITY	4.65
RELATIVE DENSITY	0.866 g/mL at 20 °C
WATER SOLUBILITY	CA.6.7 G/L AT 23 C - OECD TEST GUIDELINE 105 - SOLUBLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	LOG POW: 1.64 AT 21.7 C
AUTO-IGNITION TEMPERATURE	589 C AT 1,015 HPA (761 MMHG)
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	< 1 MM ² /S AT 25 C
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION

SURFACE TENSION	64 MN/M AT 20 C
RELATIVE VAPOUR DENSITY	4.65

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
POSSIBILITY OF HAZARDOUS REACTIONS	VAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.
CONDITIONS TO AVOID	HEAT, FLAMES AND SPARKS.
INCOMPATIBLE MATERIALS	OXIDIZING AGENTS

**HAZARDOUS
DECOMPOSITION
PRODUCTS**

OTHER DECOMPOSITION PRODUCTS - NO DATA
AVAILABLE
IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	LD50 ORAL - RAT - MALE - 4,100 MG/KG INHALATION: NO DATA AVAILABLE LD50 DERMAL - RABBIT - MALE AND FEMALE - > 2,000 MG/KG
SKIN CORROSION/IRRITATION	SKIN RABBIT RESULT: NO SKIN IRRITATION - 4 H
SERIOUS EYE DAMAGE/EYE IRRITATION	EYES RABBIT RESULT: NO EYE IRRITATION - 72 H
RESPIRATORY OR SKIN SENSITISATION	GUINEA PIG DID NOT CAUSE SENSITISATION ON LABORATORY ANIMALS. (BUEHLER TEST)
GERM CELL MUTAGENICITY	REVERSE MUTATION ASSAY S. TYPHIMURIUM RESULT: NEGATIVE MUTAGENICITY (MICRONUCLEUS TEST) RAT - MALE AND FEMALE RESULT: NEGATIVE
CARCINOGENICITY	
IARC:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.
ACGIH:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY ACGIH.
NTP:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.
OSHA:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY OSHA.

REPRODUCTIVE TOXICITY	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	NO DATA AVAILABLE
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: AF7400000 TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	
TOXICITY TO FISH	SEMI-STATIC TEST LC50 - ONCORHYNCHUS MYKISS (RAINBOW TROUT) - 240 MG/L - 96 H (OECD TEST GUIDELINE 203)
TOXICITY TO DAPHNIA AND OTHER AQUATIC INVERTEBRATES	STATIC TEST EC50 - DAPHNIA MAGNA (WATER FLEA) - 350 MG/L - 48 H (OECD TEST GUIDELINE 202)
PERSISTENCE AND DEGRADABILITY	
BIODEGRADABILITY	AEROBIC - EXPOSURE TIME 28 D RESULT: 50 % - INHERENTLY BIODEGRADABLE. (OECD TEST GUIDELINE 301D)
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL.

CONTAMINATED PACKAGING DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)
PROPER SHIPPING NAME: BUTYL ACETATES
UN NUMBER: 1123
CLASS: 3
PACKING GROUP: II
REPORTABLE QUANTITY (RQ): 5000 LBS
POISON INHALATION HAZARD: NO

IMDG
PROPER SHIPPING NAME: BUTYL ACETATES
UN NUMBER: 1123
CLASS: 3
PACKING GROUP: II
EMS-NO: F-E, S-D

IATA
PROPER SHIPPING NAME: BUTYL ACETATES
UN NUMBER: 1123
CLASS: 3
PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.

SARA 313 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DEMINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.

SARA 311/312 HAZARDS FIRE HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
<i>tert</i> -Butyl acetate	540-88-5	4/24/1993

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
<i>tert</i> -Butyl acetate	540-88-5	4/24/1993

NEW JERSEY RIGHT TO KNOW COMPONENTS

	CAS-NO.	REVISION DATE
<i>tert</i> -Butyl acetate	540-88-5	4/24/1993

CALIFORNIA PROP. 65 COMPONENTS THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE HARM.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

FLAM. LIQ. H225	FLAMMABLE LIQUIDS HIGHLY FLAMMABLE LIQUID AND VAPOUR.
--------------------	--

HMIS RATING

HEALTH HAZARD:	1
CHRONIC HEALTH HAZARD: FLAMMABILITY:	3
PHYSICAL HAZARD	0

NFPA RATING

HEALTH HAZARD:	0
FIRE HAZARD:	3
REACTIVITY HAZARD:	0

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*