# Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

## SAFETY DATA SHEET

#### SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #: 30279

NAME: Manganese(II) chloride anhydrous crystalline

SYNONYMS:

24 HOUR EMERGENCY

TELEPHONE:

(800) 535-5053(USA)

352-323-3500 (INTERNATIONAL)

TO REQUEST AN MSDS: (800) 869-9290

CUSTOMER SERVICE:

(630) 766-2112

## SECTION 2. HAZARDS IDENTIFICATION

## CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS) ACUTE TOXICITY, ORAL (CATEGORY 3), H301 SERIOUS EYE DAMAGE (CATEGORY 1), H318 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE (CATEGORY 2), BRAIN, H373

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE, INHALATION (CATEGORY 2), BRAIN, H373

SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 2), H401 LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 2), H411

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

#### GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

**PICTOGRAM** 



SIGNAL WORD DANGER

## **HAZARD STATEMENT(S)**

H301 TOXIC IF SWALLOWED.

H318 CAUSES SERIOUS EYE DAMAGE.

H373 MAY CAUSE DAMAGE TO ORGANS (BRAIN) THROUGH

PROLONGED OR REPEATED EXPOSURE.

H373 MAY CAUSE DAMAGE TO ORGANS (BRAIN) THROUGH

PROLONGED OR REPEATED EXPOSURE IF INHALED.

H411 TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

## PRECAUTIONARY STATEMENT(S)

P260 DO NOT BREATHE DUST/FUME/GAS/MIST/VAPOURS/

P264 WASH SKIN THOROUGHLY AFTER HANDLING. P270 DO NOT EAT, DRINK OR SMOKE WHEN USING THIS

PRODUCT.

P273 AVOID RELEASE TO THE ENVIRONMENT.

P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE

PROTECTION/ FACE PROTECTION.

P301 + P310 + P330IF SWALLOWED: IMMEDIATELY CALL A POISON

CENTER/DOCTOR. RINSE MOUTH.

P305 + P351 + P338 + IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL

P310 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND

EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A

POISON CENTER/DOCTOR.

P314 GET MEDICAL ADVICE/ ATTENTION IF YOU FEEL UNWELL.

P391 COLLECT SPILLAGE. P405 STORE LOCKED UP.

P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED

WASTE DISPOSAL PLANT.

HAZARDS NOT **NONE** 

**OTHERWISE** 

CLASSIFIED (HNOC) OR NOT COVERED

BY GHS

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF: MnCl<sub>2</sub>

MW: 125.84

CAS-NO. 7773-01-5

PURITY:  $\geq$  98% (Assay, metal basis)

#### HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION					
Manganese(II) chloride anhydrous crystalline							
	ACUTE TOX. 3; EYE DAM. 1;	<= 100%					
	STOT RE 2; AQUATIC ACUTE 2;						
	AQUATIC CHRONIC 2; H301,						
	H318, H373, H373, H401, H411						

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

## **SECTION 4. FIRST-AID MEASURES**

#### **DESCRIPTION OF FIRST AID MEASURES**

GENERAL ADVICE CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA

SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT

OF DANGEROUS AREA.

IF INHALED IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF

NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.

CONSULT A PHYSICIAN.

IN CASE OF SKIN

**CONTACT** 

**CONTACT** 

WASH OFF WITH SOAP AND PLENTY OF WATER. TAKE

VICTIM IMMEDIATELY TO HOSPITAL. CONSULT A

PHYSICIAN.

IN CASE OF EYE

RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT

LEAST 15 MINUTES AND CONSULT A PHYSICIAN.

**IF SWALLOWED** NEVER GIVE ANYTHING BY MOUTH TO AN

UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER.

CONSULT A PHYSICIAN.

MOST IMPORTANT

SYMPTOMS AND

EFFECTS, BOTH ACUTE AND DELAYED

THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE

SECTION 2.2) AND/OR IN SECTION 11.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT **NEEDED** 

NO DATA AVAILABLE

## SECTION 5. FIRE AND EXPLOSION DATA

**EXTINGUISHING MEDIA** 

**SUITABLE** USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY

**EXTINGUISHING MEDIA** CHEMICAL OR CARBON DIOXIDE.

SPECIAL HAZARDS HYDROGEN CHLORIDE GAS.

ARISING FROM THE MANGANESE/MANGANESE OXIDES

SUBSTANCE OR MIXTURE

ADVICE FOR WEAR SELF-CONTAINED BREATHING APPARATUS FOR

**FIREFIGHTERS** FIREFIGHTING IF NECESSARY.

FURTHER INFORMATION NO DATA AVAILABLE

## SECTION 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL** WEAR RESPIRATORY PROTECTION. AVOID DUST PRECAUTIONS. FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE **PROTECTIVE** PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST. **EQUIPMENT AND** FOR PERSONAL PROTECTION SEE SECTION 8. **EMERGENCY** 

**ENVIRONMENTAL** PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE **PRECAUTIONS** TO DO SO. DO NOT LET PRODUCT ENTER DRAINS.

DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

**METHODS AND** PICK UP AND ARRANGE DISPOSAL WITHOUT CREATING DUST. SWEEP UP AND SHOVEL. KEEP IN **MATERIALS FOR CONTAINMENT AND** SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.

REFERENCE TO OTHER FOR DISPOSAL SEE SECTION 13.

**SECTIONS** 

**CLEANING UP** 

**PROCEDURES** 

## **SECTION 7. HANDLING AND STORAGE**

PRECAUTIONS FOR SAFE AVOID CONTACT WITH SKIN AND EYES. AVOID HANDLING FORMATION OF DUST AND AEROSOLS.FURTHER

FORMATION OF DUST AND AEROSOLS.FURTHER PROCESSING OF SOLID MATERIALS MAY RESULT IN THE FORMATION OF COMBUSTIBLE DUSTS. THE POTENTIAL FOR COMBUSTIBLE DUST FORMATION SHOULD BE TAKEN INTO CONSIDERATION BEFORE

ADDITIONAL PROCESSING OCCURS.

PROVIDE APPROPRIATE EXHAUST VENTILATION AT

PLACES WHERE DUST IS FORMED. FOR PRECAUTIONS SEE SECTION 2.2.

CONDITIONS FOR SAFE STORAGE, INCLUDING

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND

WELL-VENTILATED PLACE.

ANY INCOMPATIBILITIES STORE UNDER INERT GAS. MOISTURE SENSITIVE.

Store at RT

**SPECIFIC END USE(S)** 

APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **CONTROL PARAMETERS**

## COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL	BASIS
			PARAMETERS	
Manganese(II) chloride	7773-01-5	С	5 MG/M3	USA. OCCUPATIONAL
anhydrous crystalline				EXPOSURE LIMITS (OSHA)
				- TABLE Z-1 LIMITS FOR
				AIR CONTAMINANTS
	REMARKS	CEILING LIMIT IS TO BE DETERMINED FROM		
		BREATHING-ZONE AIR SAMPLES.		
		TWA	0.1 MG/M3	USA. ACGIH THRESHOLD
				LIMIT VALUES (TLV)
		CENTRAL NERVOUS SYSTEM IMPAIRMENT		
		NOT CLASSIFIABLE AS A HUMAN CARCINOGEN		
		VARIES		
		TWA	0.02 MG/M3	USA. ACGIH THRESHOLD
				LIMIT VALUES (TLV)
		CENTRAL NERVOUS SYSTEM IMPAIRMENT		
		NOT CLASSIFIABLE AS A HUMAN CARCINOGEN VARIES		
		TWA	1 MG/M3	USA. NIOSH
				RECOMMENDED
				EXPOSURE LIMITS

S	ST	3 MG/M3	USA. NIOSH
			RECOMMENDED
			EXPOSURE LIMITS
	PEL	0.2 MG/M3	CALIFORNIA PERMISSIBLE
			EXPOSURE LIMITS FOR
			CHEMICAL
			CONTAMINANTS

#### **EXPOSURE CONTROLS**

APPROPRIATEAVOID CONTACT WITH SKIN, EYES AND CLOTHING.ENGINEERINGWASH HANDS BEFORE BREAKS AND IMMEDIATELY

**CONTROLS** AFTER HANDLING THE PRODUCT.

### PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT

FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR EN 166(EU).

**SKIN PROTECTION** HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED

PRIOR TO USE. USE PROPER GLOVE REMOVAL

TECHNIQUE (WITHOUT TOUCHING GLOVE"S OUTER

SURFACE) TO AVOID SKIN CONTACT WITH THIS

PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY

HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

SPLASH CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.11 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED: DERMATRIL (KCL 740, SIZE M)

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE

APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER

FAMILIAR WITH THE SPECIFIC SITUATION OF

ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY

SPECIFIC USE SCENARIO.

**BODY PROTECTION** COMPLETE SUIT PROTECTING AGAINST CHEMICALS,

THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE

SPECIFIC WORKPLACE.

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORY **PROTECTION** 

RESPIRATORS ARE APPROPRIATE USE A FULLFACE

PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN 143) RESPIRATOR CARTRIDGES AS A BACKUP TO

ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER

APPROPRIATE GOVERNMENT STANDARDS SUCH AS

NIOSH (US) OR CEN (EU).

**CONTROL OF ENVIRONMENTAL** 

**EXPOSURE** 

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO

DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE

AVOIDED.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Rose red crystalline powder **ODOUR** NO DATA AVAILABLE ODOUR THRESHOLD NO DATA AVAILABLE PH 5.5 AT 25 G/L AT 20 C

650 °C MELTING

POINT/FREEZING POINT

1190 °C INITIAL BOILING POINT

AND BOILING RANGE

FLASH POINT

**EVAPORATION RATE** NO DATA AVAILABLE

THE PRODUCT IS NOT FLAMMABLE. FLAMMABILITY (SOLID,

GAS)

UPPER/LOWER NO DATA AVAILABLE

FLAMMABILITY OR EXPLOSIVE LIMITS

NO DATA AVAILABLE VAPOUR PRESSURE VAPOUR DENSITY NO DATA AVAILABLE

RELATIVE DENSITY 2.98

WATER SOLUBILITY 757 G/L AT 20 C

PARTITION COEFFICIENT: NO DATA AVAILABLE

N- OCTANOL/WATER

**AUTO-IGNITION** NO DATA AVAILABLE

**TEMPERATURE** 

DECOMPOSITION NO DATA AVAILABLE

TEMPERATURE

NO DATA AVAILABLE VISCOSITY **EXPLOSIVE PROPERTIES** NO DATA AVAILABLE OXIDIZING PROPERTIES NO DATA AVAILABLE

## OTHER SAFETY INFORMATION

NO DATA AVAILABLE

## SECTION 10. STABILITY AND REACTIVITY

**REACTIVITY** NO DATA AVAILABLE

CHEMICAL STABILITY STABLE UNDER RECOMMENDED STORAGE

CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS NO DATA AVAILABLE

**CONDITIONS TO AVOID** AVOID MOISTURE.

INCOMPATIBLE ZINC, SODIUM/SODIUM OXIDES, POTASSIUM, STRONG

MATERIALS ACIDS, HYDROGEN PEROXIDE

HAZARDOUS DECOMPOSITION

**DECOMPOSITION**UNDER FIRE CONDITIONS. - HYDROGEN CHLORIDE**PRODUCTS**GAS, MANGANESE/MANGANESE OXIDES

UAS, MANUANESE/MANUANESE OAIDES

OTHER DECOMPOSITION PRODUCTS - NO DATA

HAZARDOUS DECOMPOSITION PRODUCTS FORMED

**AVAILABLE** 

IN THE EVENT OF FIRE: SEE SECTION 5

#### SECTION 11. TOXICOLOGICAL INFORMATION

### INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY LD50 ORAL - MOUSE - MALE - 1,330 MG/KG

LD50 ORAL - RAT - FEMALE - 236 MG/KG

INHALATION: NO DATA AVAILABLE

DERMAL: NO DATA AVAILABLE

NO DATA AVAILABLE

SKIN - RABBIT

**CORROSION/IRRITATION** RESULT: NO SKIN IRRITATION - 4 H

(OECD TEST GUIDELINE 404)

SERIOUS EYE EYES - RABBIT

DAMAGE/EYE IRRITATION RESULT: IRRITATING

(OECD TEST GUIDELINE 405)

RESPIRATORY OR SKIN SENSITISATION

LOCAL LYMPH NODE ASSAY (LLNA) - MOUSE

**RESULT: NEGATIVE** 

(OECD TEST GUIDELINE 429)

GERM CELL MUTAGENICITY NO DATA AVAILABLE

**CARCINOGENICITY** 

IARC: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS

IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED

HUMAN CARCINOGEN BY IARC.

NTP: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED

CARCINOGEN BY NTP.

OSHA: NO COMPONENT OF THIS PRODUCT PRESENT AT

LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA'S LIST OF REGULATED CARCINOGENS.

REPRODUCTIVE TOXICITY NO DATA AVAILABLE

SPECIFIC TARGET ORGAN

**TOXICITY - SINGLE** 

**EXPOSURE** 

NO DATA AVAILABLE

SPECIFIC TARGET ORGAN TOXICITY - REPEATED

**EXPOSURE** 

MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. - BRAIN

**ASPIRATION HAZARD** NO DATA AVAILABLE

ADDITIONAL INFORMATION

RTECS: OO9625000

MEN EXPOSED TO MANGANESE DUSTS SHOWED A DECREASE IN FERTILITY. CHRONIC MANGANESE POISONING PRIMARILY INVOLVES THE CENTRAL NERVOUS SYSTEM. EARLY SYMPTOMS INCLUDE LANGUOR, SLEEPINESS AND WEAKNESS IN THE LEGS. A STOLID MASK-LIKE APPEARANCE OF THE FACE, EMOTIONAL DISTURBANCES SUCH AS

UNCONTROLLABLE LAUGHTER AND A SPASTIC GAIT

WITH TENDENCY TO FALL IN WALKING ARE FINDINGS IN MORE ADVANCED CASES. HIGH INCIDENCE OF PNEUMONIA HAS BEEN FOUND IN WORKERS EXPOSED TO THE DUST OR FUME OF SOME MANGANESE COMPOUNDS. TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN

THOROUGHLY INVESTIGATED.

#### SECTION 12. ECOLOGICAL INFORMATION

TOXICITY

TOXICITY TO DAPHNIA AND

OTHER AQUATIC INVERTEBRATES

EC50 - DAPHNIA MAGNA (WATER FLEA) - 9.8 MG/L - 48

Η

TOXICITY TO ALGAE GROWTH INHIBITION EC50 -

PSEUDOKIRCHNERIELLA SUBCAPITATA - 3.83 MG/L -

72 H

(OECD TEST GUIDELINE 201)

PERSISTENCE AND DEGRADABILITY

NO DATA AVAILABLE

BIOACCUMULATIVE

**POTENTIAL** 

NO DATA AVAILABLE

MOBILITY IN SOIL NO DATA AVAILABLE

RESULTS OF PBT AND

VPVB ASSESSMENT

PBT/VPVB ASSESSMENT NOT AVAILABLE AS

CHEMICAL SAFETY ASSESSMENT NOT

REQUIRED/NOT CONDUCTED

**OTHER ADVERSE EFFECTS** AN ENVIRONMENTAL HAZARD CANNOT BE

EXCLUDED IN THE EVENT OF UNPROFESSIONAL

HANDLING OR DISPOSAL.

TOXIC TO AQUATIC LIFE WITH LONG LASTING

EFFECTS.

AVOID RELEASE TO THE ENVIRONMENT.

## SECTION 13. DISPOSAL CONSIDERATIONS

## WASTE TREATMENT METHODS

PRODUCT OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS

TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN

AFTERBURNER AND SCRUBBER.

CONTAMINATED PACKAGING

DISPOSE OF AS UNUSED PRODUCT.

## SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: TOXIC SOLID, INORGANIC, N.O.S. (Manganese(II) chloride

anhydrous crystalline)

UN NUMBER: 3288 CLASS: 6.1 PACKING GROUP: III

REPORTABLE QUANTITY

RO):

POISON INHALATION NO

HAZARD:

**IMDG** 

PROPER SHIPPING NAME: TOXIC SOLID, INORGANIC, N.O.S. (Manganese(II) chloride

anhydrous crystalline)

UN NUMBER: 3288
CLASS: 6.1
PACKING GROUP: III
EMS-NO: F-A, S-A

**IATA** 

PROPER SHIPPING NAME: TOXIC SOLID, INORGANIC, N.O.S. (Manganese(II) chloride

anhydrous crystalline)

UN NUMBER: 3288 CLASS: 6.1 PACKING GROUP: III

## SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY

COMPONENTS WITH A SECTION 302 EHS TPQ.

**SARA 313 COMPONENTS** 

THE FOLLOWING COMPONENTS ARE SUBJECT TO REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:

CAS-NO. REVISION DATE

Manganese(II) chloride 7773-01-5 07-08-2015

anhydrous crystalline

SARA 311/312 HAZARDS ACUTE HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

PENNSYLVANIA RIGHT TO KNOW COMPONENTS

Manganese(II) chloride anhydrous crystalline

#### SECTION 16. OTHER INFORMATION

## FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H301 TOXIC IF SWALLOWED.

H318 CAUSES SERIOUS EYE DAMAGE.

H373 MAY CAUSE DAMAGE TO ORGANS (BRAIN) THROUGH

PROLONGED OR REPEATED EXPOSURE.

H373 MAY CAUSE DAMAGE TO ORGANS (BRAIN) THROUGH

PROLONGED OR REPEATED EXPOSURE IF INHALED.

H411 TOXIC TO AQUATIC LIFE WITH LONG LASTING

**EFFECTS** 

MSDS LEGEND

MW: MOLECULAR WEIGHT MF: MOLECULAR FORMULA

VOC: VOLATILE ORGANIC COMPOUNDS

ACGIH: AMERICAN CONFERENCE OF GOVERNMENENTAL INDUSTRIAL

**HYGINISTS** 

CAS: CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

PEL: PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV: THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.1. REVISION DATE: 01/27/2017