

Chem-Impex International Inc.

Tel: (630) 766-2112
E-mail: sales@chemimpex.com
Shipping and Correspondence:
935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218
Web site: www.chemimpex.com
Manufacturing site:
825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	30298
NAME:	Bismuth(III) bromide
SYNONYMS:	
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)
SKIN CORROSION (CATEGORY 1B), H314
SERIOUS EYE DAMAGE (CATEGORY 1), H318

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE
SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

PRECAUTIONARY STATEMENT(S)

P260 DO NOT BREATHE DUST OR MIST.
P264 WASH SKIN THOROUGHLY AFTER HANDLING.
P280 WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.
P301 + P330 + P331 IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING.
P303 + P361 + P353 IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER.
P304 + P340 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING.
P305 + P351 + P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.
P310 IMMEDIATELY CALL A POISON CENTER OR DOCTOR/ PHYSICIAN.
P321 SPECIFIC TREATMENT (SEE SUPPLEMENTAL FIRST AID INSTRUCTIONS ON THIS LABEL).
P363 WASH CONTAMINATED CLOTHING BEFORE REUSE.
P405 STORE LOCKED UP.
P501 DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

**HAZARDS NOT
OTHERWISE
CLASSIFIED (HNOC)
OR NOT COVERED
BY GHS** NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:	BiBr ₃
MW:	448.69
CAS-NO.	7787-58-8
PURITY:	≥ 99% (Metals basis)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
BISMUTH TRIBROMIDE		
	SKIN CORR. 1B; EYE DAM. 1; STOT SE 3; H314, H318, H335	<= 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.
IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	TAKE OFF CONTAMINATED CLOTHING AND SHOES IMMEDIATELY. WASH OFF WITH SOAP AND PLENTY OF WATER. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	RINSE THOROUGHLY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN.CONTINUE RINSING EYES DURING TRANSPORT TO HOSPITAL.
IF SWALLOWED	DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	USE WATER SPRAY, ALCOHOL-RESISTANT FOAM, DRY CHEMICAL OR CARBON DIOXIDE.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	HYDROGEN BROMIDE GAS, BISMUTH OXIDES
ADVICE FOR FIREFIGHTERS	WEAR SELF-CONTAINED BREATHING APPARATUS FOR FIREFIGHTING IF NECESSARY.
FURTHER INFORMATION	NO DATA AVAILABLE

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES	USE PERSONAL PROTECTIVE EQUIPMENT. AVOID DUST FORMATION. AVOID BREATHING VAPOURS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. EVACUATE PERSONNEL TO SAFE AREAS. AVOID BREATHING DUST. FOR PERSONAL PROTECTION SEE SECTION 8.
ENVIRONMENTAL PRECAUTIONS	DO NOT LET PRODUCT ENTER DRAINS.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	PICK UP AND ARRANGE DISPOSAL WITHOUT CREATING DUST. SWEEP UP AND SHOVEL. KEEP IN SUITABLE, CLOSED CONTAINERS FOR DISPOSAL.
REFERENCE TO OTHER SECTIONS	FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	AVOID FORMATION OF DUST AND AEROSOLS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED. NORMAL MEASURES FOR PREVENTIVE FIRE PROTECTION. FOR PRECAUTIONS SEE SECTION 2.2.
CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES	KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. MOISTURE SENSITIVE. KEEP IN A DRY PLACE.

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2
NO OTHER SPECIFIC USES ARE STIPULATED

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

**COMPONENTS WITH
WORKPLACE CONTROL
PARAMETERS**

CONTAINS NO SUBSTANCES WITH OCCUPATIONAL
EXPOSURE LIMIT VALUES.

EXPOSURE CONTROLS

**APPROPRIATE
ENGINEERING
CONTROLS**

HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL
HYGIENE AND SAFETY PRACTICE. WASH HANDS
BEFORE BREAKS AND AT THE END OF WORKDAY.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

FACE SHIELD AND SAFETY GLASSES USE EQUIPMENT
FOR EYE PROTECTION TESTED AND APPROVED UNDER
APPROPRIATE GOVERNMENT STANDARDS SUCH AS
NIOSH (US) OR EN 166(EU).

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED
PRIOR TO USE. USE PROPER GLOVE REMOVAL
TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER
SURFACE) TO AVOID SKIN CONTACT WITH THIS
PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER
USE IN ACCORDANCE WITH APPLICABLE LAWS AND
GOOD LABORATORY PRACTICES. WASH AND DRY
HANDS.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS,
THE TYPE OF PROTECTIVE EQUIPMENT MUST BE
SELECTED ACCORDING TO THE CONCENTRATION AND
AMOUNT OF THE DANGEROUS SUBSTANCE AT THE
SPECIFIC WORKPLACE.

**RESPIRATORY
PROTECTION**

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING
RESPIRATORS ARE APPROPRIATE USE A FULL-FACE
PARTICLE RESPIRATOR TYPE N100 (US) OR TYPE P3 (EN
143) RESPIRATOR CARTRIDGES AS A BACKUP TO
ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE
SOLE MEANS OF PROTECTION, USE A FULL-FACE
SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND
COMPONENTS TESTED AND APPROVED UNDER
APPROPRIATE GOVERNMENT STANDARDS SUCH AS
NIOSH (US) OR CEN (EU).

**CONTROL OF
ENVIRONMENTAL
EXPOSURE**

DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Light yellow-gray crystals or powder
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING	218 °C
POINT/FREEZING POINT	
INITIAL BOILING POINT	453 °C
AND BOILING RANGE	
FLASH POINT	
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER	NO DATA AVAILABLE
FLAMMABILITY OR EXPLOSIVE LIMITS	
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	5.72
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION	NO DATA AVAILABLE
TEMPERATURE	
DECOMPOSITION	NO DATA AVAILABLE
TEMPERATURE	
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	NO DATA AVAILABLE

OTHER SAFETY INFORMATION	NO DATA AVAILABLE
-------------------------------------	-------------------

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	STABLE UNDER RECOMMENDED STORAGE CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	AIR AVOID MOISTURE.
INCOMPATIBLE MATERIALS	ACIDS
HAZARDOUS DECOMPOSITION PRODUCTS	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - HYDROGEN BROMIDE GAS, BISMUTH OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	NO DATA AVAILABLE INHALATION: IRRITATING TO RESPIRATORY SYSTEM. DERMAL: NO DATA AVAILABLE NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	NO DATA AVAILABLE
SERIOUS EYE DAMAGE/EYE IRRITATION	CAUSES SERIOUS EYE DAMAGE.
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE
GERM CELL MUTAGENICITY	NO DATA AVAILABLE
CARCINOGENICITY	
IARC:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED HUMAN CARCINOGEN BY IARC.
ACGIH:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A CARCINOGEN OR POTENTIAL CARCINOGEN BY ACGIH.

NTP:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP.
OSHA:	NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.
REPRODUCTIVE TOXICITY	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	MAY CAUSE RESPIRATORY IRRITATION.
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	NO DATA AVAILABLE
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: NOT AVAILABLE SYMPTOMS OF CHRONIC BISMUTH TOXICITY IN HUMANS CONSISTS OF DECREASED APPETITE, WEAKNESS, RHEUMATIC PAIN, DIARRHEA, FEVER, METAL LINE ON THE GUMS, FOUL BREATHE, GINGIVITIS, AND DERMATITIS. JAUNDICE AND CONJUNCTIVAL HEMORRHAGE ARE RARE, BUT HAVE BEEN REPORTED. BISMUTH NEPHROPATHY WITH PROTEINURIA MAY OCCUR. THE KIDNEY IS THE SITE OF HIGHEST CONCENTRATION WITH THE LIVER BEING CONSIDERABLY LOWER. BISMUTH DOES PASS INTO THE AMNIOTIC FLUID AND INTO THE FETUS. MATERIAL IS EXTREMELY DESTRUCTIVE TO TISSUE OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT, EYES, AND SKIN, COUGH, SHORTNESS OF BREATH, HEADACHE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	NO DATA AVAILABLE
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE

**RESULTS OF PBT AND
VPVB ASSESSMENT**

PBT/VPVB ASSESSMENT NOT AVAILABLE AS
CHEMICAL SAFETY ASSESSMENT NOT
REQUIRED/NOT CONDUCTED

OTHER ADVERSE EFFECTS

DISCHARGE INTO THE ENVIRONMENT MUST BE
AVOIDED.

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT

OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS
TO A LICENSED DISPOSAL COMPANY. CONTACT A
LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE
TO DISPOSE OF THIS MATERIAL. DISSOLVE OR MIX THE
MATERIAL WITH A COMBUSTIBLE SOLVENT AND BURN
IN A CHEMICAL INCINERATOR EQUIPPED WITH AN
AFTERBURNER AND SCRUBBER.

**CONTAMINATED
PACKAGING**

DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.(
BISMUTH TRIBROMIDE)
UN NUMBER: 3260
CLASS: 8
PACKING GROUP: II
POISON INHALATION HAZARD: NO

IMDG

PROPER SHIPPING NAME: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.(
BISMUTH TRIBROMIDE)
UN NUMBER: 3260
CLASS: 8
PACKING GROUP: II
EMS-NO: F-A, S-B

IATA

PROPER SHIPPING NAME: CORROSIVE SOLID, ACIDIC, INORGANIC, N.O.S.(
BISMUTH TRIBROMIDE)
UN NUMBER: 3260
CLASS: 8

PACKING GROUP: II

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS	NO CHEMICALS IN THIS MATERIAL ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III, SECTION 302.	
SARA 313 COMPONENTS	THIS MATERIAL DOES NOT CONTAIN ANY CHEMICAL COMPONENTS WITH KNOWN CAS NUMBERS THAT EXCEED THE THRESHOLD (DEMINIMIS) REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313.	
SARA 311/312 HAZARDS	ACUTE HEALTH HAZARD	
MASSACHUSETTS RIGHT TO KNOW COMPONENTS	NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.	
PENNSYLVANIA RIGHT TO KNOW COMPONENTS	CAS-NO.	REVISION DATE
Bismuth(III) bromide	7787-58-8	
NEW JERSEY RIGHT TO KNOW COMPONENTS	CAS-NO.	REVISION DATE
Bismuth(III) bromide	7787-58-8	
CALIFORNIA PROP. 65 COMPONENTS	THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR ANY OTHER REPRODUCTIVE HARM.	

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.
H314 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
CAS:	CHEMICAL ABSTRACTS SERVICE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION:3.1.

REVISION DATE: 01/27/2017