

Chem-Impex International Inc.

Tel: (630) 766-2112

E-mail: sales@chemimpex.com

Shipping and Correspondence:

935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218

Web site: www.chemimpex.com

Manufacturing site:

825 Dillon Drive
Wood Dale, IL 60191 USA

SAFETY DATA SHEET

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	30685
NAME:	Nickel (II) nitrate hexahydrate
SYNONYMS:	
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

OXIDIZING SOLIDS (CATEGORY 2), H272
ACUTE TOXICITY, ORAL (CATEGORY 4), H302
ACUTE TOXICITY, INHALATION (CATEGORY 4), H332
SKIN IRRITATION (CATEGORY 2), H315
SERIOUS EYE DAMAGE (CATEGORY 1), H318
RESPIRATORY SENSITISATION (CATEGORY 1), H334

SKIN SENSITISATION (CATEGORY 1), H317
GERM CELL MUTAGENICITY (CATEGORY 2), H341
CARCINOGENICITY (CATEGORY 1A), H350
REPRODUCTIVE TOXICITY (CATEGORY 1B), H360
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE, INHALATION (CATEGORY 1), H372
SHORT-TERM (ACUTE) AQUATIC HAZARD (CATEGORY 1), H400
LONG-TERM (CHRONIC) AQUATIC HAZARD (CATEGORY 1), H410

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS

PICTOGRAM



SIGNAL WORD

DANGER

HAZARD STATEMENT(S)

H272	MAY INTENSIFY FIRE; OXIDIZER.
H302 + H332	HARMFUL IF SWALLOWED OR IF INHALED
H315	CAUSES SKIN IRRITATION.
H317	MAY CAUSE AN ALLERGIC SKIN REACTION.
H318	CAUSES SERIOUS EYE DAMAGE.
H334	MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.
H341	SUSPECTED OF CAUSING GENETIC DEFECTS.
H350	MAY CAUSE CANCER.
H360	MAY DAMAGE FERTILITY OR THE UNBORN CHILD.
H372	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE IF INHALED.
H410	VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT(S)

P201	OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.
P202	DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.
P210	KEEP AWAY FROM HEAT.
P220	KEEP/STORE AWAY FROM CLOTHING/ COMBUSTIBLE MATERIALS.
P221	TAKE ANY PRECAUTION TO AVOID MIXING WITH COMBUSTIBLES.
P260	DO NOT BREATHE DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
P264	WASH SKIN THOROUGHLY AFTER HANDLING.
P270	DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P272	CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.
P273	AVOID RELEASE TO THE ENVIRONMENT.
P280	WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION.
P285	IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION.

P301 + P312 + P330	IF SWALLOWED: CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL. RINSE MOUTH.
P302 + P352	IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.
P304 + P340 + P312	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.
P305 + P351 + P338 + P310	IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A POISON CENTER/DOCTOR.
P308 + P313	IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ ATTENTION.
P333 + P313	IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ ATTENTION.
P362	TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE.
P370 + P378	IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM TO EXTINGUISH.
P391	COLLECT SPILLAGE.
P405	STORE LOCKED UP.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.
HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS	NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:	Ni(NO ₃) ₂ ·6H ₂ O
MW:	290.79
CAS-NO.	13478-00-7
PURITY:	≥ 99% 19 - 21% (as Nickel, complexometry), ≤ 100 ppm (Other trace metal impurity)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
Nickel (II) nitrate hexahydrate		
	OX. SOL. 2; ACUTE TOX. 4; SKIN IRRIT. 2; EYE DAM. 1; RESP. SENS. 1; SKIN SENS. 1; MUTA. 2; CARC. 1A; REPR. 1B; STOT RE 1; AQUATIC ACUTE 1; AQUATIC CHRONIC 1; H272, H302, H332,	≤ 100 %

	H315, H318, H334, H317, H341, H350, H360, H372, H400, H410 CONCENTRATION LIMITS: >= 1 %: STOT RE 1, H372; 0.1 - < 1 %: STOT RE 2, H373; >= 20 %: SKIN IRRIT. 2, H315; >= 0.01 %: SKIN SENS. 1, H317 M-FACTOR - AQUATIC ACUTE: 10 - AQUATIC CHRONIC: 10	
--	--	--

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE	FIRST AIDER NEEDS TO PROTECT HIMSELF. SHOW THIS MATERIAL SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.
IF INHALED	AFTER INHALATION: FRESH AIR. CALL IN PHYSICIAN.
IN CASE OF SKIN CONTACT	IN CASE OF SKIN CONTACT: TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER. CONSULT A PHYSICIAN.
IN CASE OF EYE CONTACT	AFTER EYE CONTACT: RINSE OUT WITH PLENTY OF WATER. IMMEDIATELY CALL IN OPHTHALMOLOGIST. REMOVE CONTACT LENSES.
IF SWALLOWED	AFTER SWALLOWING: IMMEDIATELY MAKE VICTIM DRINK WATER (TWO GLASSES AT MOST). CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11.
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA
USE EXTINGUISHING MEASURES THAT ARE APPROPRIATE
TO LOCAL CIRCUMSTANCES AND THE SURROUNDING
ENVIRONMENT.

UNSUITABLE EXTINGUISHING MEDIA
FOR THIS SUBSTANCE/MIXTURE NO LIMITATIONS OF
EXTINGUISHING AGENTS ARE GIVEN.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

NICKEL/NICKEL OXIDES
NOT COMBUSTIBLE.
HAS A FIRE-PROMOTING EFFECT DUE TO RELEASE OF
OXYGEN.
AMBIENT FIRE MAY LIBERATE HAZARDOUS VAPOURS.

ADVICE FOR FIREFIGHTERS

STAY IN DANGER AREA ONLY WITH SELF-CONTAINED
BREATHING APPARATUS. PREVENT SKIN CONTACT BY
KEEPING A SAFE DISTANCE OR BY WEARING SUITABLE
PROTECTIVE CLOTHING.

FURTHER INFORMATION

SUPPRESS (KNOCK DOWN) GASES/VAPORS/MISTS WITH A
WATER SPRAY JET. PREVENT FIRE EXTINGUISHING WATER
FROM CONTAMINATING SURFACE WATER OR THE
GROUND WATER SYSTEM.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

ADVICE FOR NON-EMERGENCY PERSONNEL: AVOID
GENERATION AND INHALATION OF DUSTS IN ALL
CIRCUMSTANCES. AVOID SUBSTANCE CONTACT. ENSURE
ADEQUATE VENTILATION. EVACUATE THE DANGER AREA,
OBSERVE EMERGENCY PROCEDURES, CONSULT AN
EXPERT.

FOR PERSONAL PROTECTION SEE SECTION 8.

ENVIRONMENTAL PRECAUTIONS

DO NOT LET PRODUCT ENTER DRAINS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

COVER DRAINS. COLLECT, BIND, AND PUMP OFF SPILLS.
OBSERVE POSSIBLE MATERIAL RESTRICTIONS (SEE
SECTIONS 7 AND 10). TAKE UP CAREFULLY. DISPOSE OF
PROPERLY. CLEAN UP AFFECTED AREA. AVOID
GENERATION OF DUSTS.

**REFERENCE TO OTHER
SECTIONS**

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE
HANDLING**

WORK UNDER HOOD. DO NOT INHALE
SUBSTANCE/MIXTURE.
KEEP AWAY FROM OPEN FLAMES, HOT SURFACES AND
SOURCES OF IGNITION.
FOR PRECAUTIONS SEE SECTION 2.2.

**CONDITIONS FOR SAFE
STORAGE, INCLUDING
ANY INCOMPATIBILITIES**

KEEP LOCKED UP OR IN AN AREA ACCESSIBLE ONLY TO
QUALIFIED OR AUTHORIZED PERSONS. DO NOT STORE
NEAR COMBUSTIBLE MATERIALS.
HYGROSCOPIC.

Store at RT

SPECIFIC END USE(S)

APART FROM THE USES MENTIONED IN SECTION 1.2 NO
OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
Nickel (II) nitrate hexahydrate	13478-00-7	TWA	1 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		TWA	0.1 MG/M3	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
	REMARKS	LUNG DAMAGE NASAL CANCER NOT CLASSIFIABLE AS A HUMAN CARCINOGEN VARIES		
		TWA	0.015 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
		POTENTIAL OCCUPATIONAL CARCINOGEN SEE APPENDIX A		

		PEL	0.05 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS
--	--	-----	------------	--

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS IMMEDIATELY CHANGE CONTAMINATED CLOTHING. APPLY PREVENTIVE SKIN PROTECTION. WASH HANDS AND FACE AFTER WORKING WITH SUBSTANCE.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION USE EQUIPMENT FOR EYE PROTECTION TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR EN 166(EU). TIGHTLY FITTING SAFETY GOGGLES

SKIN PROTECTION HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

BODY PROTECTION PROTECTIVE CLOTHING

RESPIRATORY PROTECTION REQUIRED WHEN DUSTS ARE GENERATED. OUR RECOMMENDATIONS ON FILTERING RESPIRATORY PROTECTION ARE BASED ON THE FOLLOWING STANDARDS: DIN EN 143, DIN 14387 AND OTHER ACCOMPANYING STANDARDS RELATING TO THE USED RESPIRATORY PROTECTION SYSTEM.

CONTROL OF ENVIRONMENTAL EXPOSURE DO NOT LET PRODUCT ENTER DRAINS.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Green to green blue crystal/ crystalline powder
ODOUR	NO DATA AVAILABLE
ODOUR THRESHOLD	NO DATA AVAILABLE
PH	NO DATA AVAILABLE
MELTING	56 °C
POINT/FREEZING POINT	
INITIAL BOILING POINT	
AND BOILING RANGE	
FLASH POINT	

EVAPOURATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	NO DATA AVAILABLE
VAPOUR PRESSURE	NO DATA AVAILABLE
VAPOUR DENSITY	NO DATA AVAILABLE
RELATIVE DENSITY	2.05
WATER SOLUBILITY	NO DATA AVAILABLE
PARTITION COEFFICIENT: N- OCTANOL/WATER	NO DATA AVAILABLE
AUTO-IGNITION TEMPERATURE	NO DATA AVAILABLE
DECOMPOSITION TEMPERATURE	NO DATA AVAILABLE
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE PROPERTIES	NO DATA AVAILABLE
OXIDIZING PROPERTIES	THE SUBSTANCE OR MIXTURE IS CLASSIFIED AS OXIDIZING WITH THE CATEGORY 2.
OTHER SAFETY INFORMATION	NO DATA AVAILABLE

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	NO DATA AVAILABLE
CHEMICAL STABILITY	THE PRODUCT IS CHEMICALLY STABLE UNDER STANDARD AMBIENT CONDITIONS
POSSIBILITY OF HAZARDOUS REACTIONS	NO DATA AVAILABLE
CONDITIONS TO AVOID	NO DATA AVAILABLE
INCOMPATIBLE MATERIALS	ORGANIC MATERIALS, POWDERED METALS, STRONG REDUCING AGENTS, ACIDS
HAZARDOUS DECOMPOSITION PRODUCTS	HAZARDOUS DECOMPOSITION PRODUCTS FORMED UNDER FIRE CONDITIONS. - NICKEL/NICKEL OXIDES OTHER DECOMPOSITION PRODUCTS - NO DATA AVAILABLE IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	LD50 ORAL - RAT - 1,620 MG/KG INHALATION: NO DATA AVAILABLE DERMAL: NO DATA AVAILABLE NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	NO DATA AVAILABLE
SERIOUS EYE DAMAGE/EYE IRRITATION	NO DATA AVAILABLE
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE
GERM CELL MUTAGENICITY	IN VITRO TESTS SHOWED MUTAGENIC EFFECTS WHICH WERE NOT OBSERVED WITH IN VIVO TEST.
CARCINOGENICITY HUMAN CARCINOGEN. IARC: NTP: OSHA:	1 - GROUP 1: CARCINOGENIC TO HUMANS NO INGREDIENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS IDENTIFIED AS A KNOWN OR ANTICIPATED CARCINOGEN BY NTP. NO COMPONENT OF THIS PRODUCT PRESENT AT LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON OSHA S LIST OF REGULATED CARCINOGENS.
REPRODUCTIVE TOXICITY	PRESUMED HUMAN REPRODUCTIVE TOXICANT
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	NO DATA AVAILABLE
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	INHALATION - CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.
ASPIRATION HAZARD	NO DATA AVAILABLE
ADDITIONAL INFORMATION	RTECS: QR7300000 TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED. STOMACH - IRREGULARITIES - BASED ON HUMAN EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY	NO DATA AVAILABLE
PERSISTENCE AND DEGRADABILITY	NO DATA AVAILABLE
BIOACCUMULATIVE POTENTIAL	NO DATA AVAILABLE
MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED.
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH THE NATIONAL AND LOC NO MIXING WITH OTHER WASTE.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)	
PROPER SHIPPING NAME:	NICKEL NITRATE
UN NUMBER:	2725
CLASS:	5.1
PACKING GROUP:	III
REPORTABLE QUANTITY (RQ):	
POISON INHALATION HAZARD:	NO
IMDG	

PROPER SHIPPING NAME: NICKEL NITRATE
UN NUMBER: 2725
CLASS: 5.1
PACKING GROUP: III
EMS-NO: F-A, S-Q
MARINE POLLUTANT: YES

IATA

PROPER SHIPPING NAME: NICKEL NITRATE
UN NUMBER: 2725
CLASS: 5.1
PACKING GROUP: III

SECTION 15. REGULATORY INFORMATION

SARA 302 COMPONENTS THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 302 EHS TPQ.

SARA 313 COMPONENTS

THE FOLLOWING COMPONENTS ARE SUBJECT TO REPORTING LEVELS ESTABLISHED BY SARA TITLE III, SECTION 313:

	CAS-NO.	REVISION DATE
Nickel (II) nitrate hexahydrate	13478-00-7	04-24-1993

SARA 311/312 HAZARDS REACTIVITY HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

MASSACHUSETTS RIGHT TO KNOW COMPONENTS

NO COMPONENTS ARE SUBJECT TO THE MASSACHUSETTS RIGHT TO KNOW ACT.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H272	MAY INTENSIFY FIRE; OXIDIZER.
H302 + H332	HARMFUL IF SWALLOWED OR IF INHALED
H315	CAUSES SKIN IRRITATION.
H317	MAY CAUSE AN ALLERGIC SKIN REACTION.
H318	CAUSES SERIOUS EYE DAMAGE.
H334	MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED.
H341	SUSPECTED OF CAUSING GENETIC DEFECTS.
H350	MAY CAUSE CANCER.
H360	MAY DAMAGE FERTILITY OR THE UNBORN CHILD.
H372	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE IF INHALED.
H410	VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

*THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL **CII** BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF **CII** HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.*

VERSION : 3.2

REVISION DATE : 07/01/2020