

Chem-Impex International Inc.

Tel: (630) 766-2112

E-mail: sales@chemimpex.com

Shipping and Correspondence:

935 Dillon Drive
Wood Dale, IL 60191 USA

Fax: (630) 766-2218

Web site: www.chemimpex.com

Manufacturing site:

825 Dillon Drive
Wood Dale, IL 60191 USA

S A F E T Y D A T A S H E E T

SECTION 1. CHEMICAL IDENTIFICATION

CATALOG #:	33877
NAME:	1-Butanol
SYNONYMS:	n-Butyl alcohol
24 HOUR EMERGENCY TELEPHONE:	(800) 535-5053(USA) 352-323-3500 (INTERNATIONAL)
TO REQUEST AN MSDS:	(800) 869-9290
CUSTOMER SERVICE:	(630) 766-2112

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS CLASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS)

FLAMMABLE LIQUIDS (CATEGORY 3), H226
ACUTE TOXICITY, ORAL (CATEGORY 4), H302
SKIN IRRITATION (CATEGORY 2), H315

SERIOUS EYE DAMAGE (CATEGORY 1), H318
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (CATEGORY 3),
RESPIRATORY SYSTEM, CENTRAL NERVOUS SYSTEM, H335, H336

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE
SECTION 16.

**GHS LABEL ELEMENTS, INCLUDING PRECAUTIONARY STATEMENTS
PICTOGRAM**



SIGNAL WORD DANGER

HAZARD STATEMENT(S)

H226	FLAMMABLE LIQUID AND VAPOUR.
H302	HARMFUL IF SWALLOWED.
H315	CAUSES SKIN IRRITATION.
H318	CAUSES SERIOUS EYE DAMAGE.
H335	MAY CAUSE RESPIRATORY IRRITATION.
H336	MAY CAUSE DROWSINESS OR DIZZINESS.

PRECAUTIONARY STATEMENT(S)

P210	KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.
P233	KEEP CONTAINER TIGHTLY CLOSED.
P240	GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.
P241	USE EXPLOSION-PROOF ELECTRICAL/ VENTILATING/ LIGHTING/ EQUIPMENT.
P242	USE ONLY NON-SPARKING TOOLS.
P243	TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.
P261	AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPOURS/ SPRAY.
P264	WASH SKIN THOROUGHLY AFTER HANDLING.
P270	DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.
P271	USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA
P280	WEAR PROTECTIVE GLOVES/ EYE PROTECTION/ FACE PROTECTION.
P301 + P312 + P330	IF SWALLOWED: CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL. RINSE MOUTH.
P303 + P361 + P353	IF ON SKIN (OR HAIR): REMOVE/ TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER.
P304 + P340 + P312	IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.
P305 + P351 + P338 + P310	IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A POISON CENTER/DOCTOR.
P332 + P313	IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ ATTENTION.

P362	TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE.
P370 + P378	IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL-RESISTANT FOAM FOR EXTINCTION.
P403 + P233	STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.
P403 + P235	STORE IN A WELL-VENTILATED PLACE. KEEP COOL.
P405	STORE LOCKED UP.
P501	DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS

NONE

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MF:	C ₄ H ₁₀ O
MW:	74.12
CAS-NO.	71-36-3
PURITY:	≥ 99% (GC)

HAZARDOUS COMPONENTS

COMPONENT	CLASSIFICATION	CONCENTRATION
N-BUTANOL	FLAM. LIQ. 3; ACUTE TOX. 4; SKIN IRRIT. 2; EYE DAM. 1; STOT SE 3; H226, H302, H315, H318, H335, H336 CONCENTRATION LIMITS: >= 20 %: STOT SE 3, H335; >= 20 %: STOT SE 3, H336	<= 100 %

FOR THE FULL TEXT OF THE H-STATEMENTS MENTIONED IN THIS SECTION, SEE SECTION 16.

SECTION 4. FIRST-AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

GENERAL ADVICE

CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE.MOVE OUT OF DANGEROUS AREA.

IF INHALED	IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.
IN CASE OF SKIN CONTACT	TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/ SHOWER.
IN CASE OF EYE CONTACT	RINSE OUT WITH PLENTY OF WATER. IMMEDIATELY CALL IN OPHTHALMOLOGIST. REMOVE CONTACT LENSES.
IF SWALLOWED	IMMEDIATELY MAKE VICTIM DRINK WATER (TWO GLASSES AT MOST). CONSULT A PHYSICIAN.
MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED	THE MOST IMPORTANT KNOWN SYMPTOMS AND EFFECTS ARE DESCRIBED IN THE LABELLING (SEE SECTION 2.2) AND/OR IN SECTION 11.
INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED	NO DATA AVAILABLE

SECTION 5. FIRE AND EXPLOSION DATA

EXTINGUISHING MEDIA

SUITABLE EXTINGUISHING MEDIA	SUITABLE EXTINGUISHING MEDIA CARBON DIOXIDE (CO ₂) FOAM DRY POWDER
	UNSUITABLE EXTINGUISHING MEDIA FOR THIS SUBSTANCE/MIXTURE NO LIMITATIONS OF EXTINGUISHING AGENTS ARE GIVEN.
SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE	CARBON OXIDES FLASH BACK POSSIBLE OVER CONSIDERABLE DISTANCE. COMBUSTIBLE. VAPORS ARE HEAVIER THAN AIR AND MAY SPREAD ALONG FLOORS. FORMS EXPLOSIVE MIXTURES WITH AIR AT ELEVATED TEMPERATURES. DEVELOPMENT OF HAZARDOUS COMBUSTION GASES OR VAPOURS POSSIBLE IN THE EVENT OF FIRE.
ADVICE FOR FIREFIGHTERS	STAY IN DANGER AREA ONLY WITH SELF-CONTAINED BREATHING APPARATUS. PREVENT SKIN CONTACT BY KEEPING A SAFE DISTANCE OR BY WEARING SUITABLE PROTECTIVE CLOTHING.

**FURTHER
INFORMATION**

IN CASE OF FIRE: EVACUATE AREA. FIGHT FIRE REMOTELY DUE TO THE RISK OF EXPLOSION. REMOVE CONTAINER FROM DANGER ZONE AND COOL WITH WATER. PREVENT FIRE EXTINGUISHING WATER FROM CONTAMINATING SURFACE WATER OR THE GROUND WATER SYSTEM.

SECTION 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL
PRECAUTIONS,
PROTECTIVE
EQUIPMENT AND
EMERGENCY
PROCEDURES**

ADVICE FOR NON-EMERGENCY PERSONNEL: DO NOT BREATHE VAPORS, AEROSOLS. AVOID SUBSTANCE CONTACT. ENSURE ADEQUATE VENTILATION. KEEP AWAY FROM HEAT AND SOURCES OF IGNITION. EVACUATE THE DANGER AREA, OBSERVE EMERGENCY PROCEDURES, CONSULT AN EXPERT.
FOR PERSONAL PROTECTION SEE SECTION 8.

**ENVIRONMENTAL
PRECAUTIONS**

DO NOT LET PRODUCT ENTER DRAINS. RISK OF EXPLOSION.

**METHODS AND
MATERIALS FOR
CONTAINMENT AND
CLEANING UP**

COVER DRAINS. COLLECT, BIND, AND PUMP OFF SPILLS. OBSERVE POSSIBLE MATERIAL RESTRICTIONS (SEE SECTIONS 7 AND 10). TAKE UP WITH LIQUID-ABSORBENT MATERIAL. DISPOSE OF PROPERLY. CLEAN UP AFFECTED AREA.

**REFERENCE TO OTHER
SECTIONS**

FOR DISPOSAL SEE SECTION 13.

SECTION 7. HANDLING AND STORAGE

**PRECAUTIONS FOR
SAFE HANDLING**

WORK UNDER HOOD. DO NOT INHALE SUBSTANCE/MIXTURE. AVOID GENERATION OF VAPOURS/AEROSOLS.
KEEP AWAY FROM OPEN FLAMES, HOT SURFACES AND SOURCES OF IGNITION. TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.
IMMEDIATELY CHANGE CONTAMINATED CLOTHING. APPLY PREVENTIVE SKIN PROTECTION. WASH HANDS AND FACE AFTER WORKING WITH SUBSTANCE.
FOR PRECAUTIONS SEE SECTION 2.2.

**CONDITIONS FOR SAFE
STORAGE, INCLUDING
ANY
INCOMPATIBILITIES**

KEEP CONTAINER TIGHTLY CLOSED IN A DRY AND WELL-VENTILATED PLACE. KEEP AWAY FROM HEAT AND SOURCES OF IGNITION.

HANDLE AND STORE UNDER INERT GAS. HYGROSCOPIC!

STORE AT RT

STORAGE CLASS (TRGS 510): 3: FLAMMABLE LIQUIDS

SPECIFIC END USE(S) APART FROM THE USES MENTIONED IN SECTION 1.2 NO OTHER SPECIFIC USES ARE STIPULATED.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

COMPONENTS WITH WORKPLACE CONTROL PARAMETERS

COMPONENT	CAS-NO.	VALUE	CONTROL PARAMETERS	BASIS
N-BUTANOL	71-36-3	TWA	20 PPM	USA. ACGIH THRESHOLD LIMIT VALUES (TLV)
		C	50 PPM 150 MG/M3	USA. NIOSH RECOMMENDED EXPOSURE LIMITS
	REMARKS	POTENTIAL FOR DERMAL ABSORPTION		
		TWA	100 PPM 300 MG/M3	USA. OCCUPATIONAL EXPOSURE LIMITS (OSHA) - TABLE Z-1 LIMITS FOR AIR CONTAMINANTS
		C	50 PPM 150 MG/M3	CALIFORNIA PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS (TITLE 8, ARTICLE 107)
		SKIN		

EXPOSURE CONTROLS

APPROPRIATE ENGINEERING CONTROLS

IMMEDIATELY CHANGE CONTAMINATED CLOTHING.
APPLY PREVENTIVE SKIN PROTECTION. WASH HANDS
AND FACE AFTER WORKING WITH SUBSTANCE.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION

USE EQUIPMENT FOR EYE PROTECTION TESTED AND
APPROVED UNDER APPROPRIATE GOVERNMENT
STANDARDS SUCH AS NIOSH (US) OR EN 166(EU).
TIGHTLY FITTING SAFETY GOGGLES

SKIN PROTECTION

HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. DISPOSE OF CONTAMINATED GLOVES AFTER USE IN ACCORDANCE WITH APPLICABLE LAWS AND GOOD LABORATORY PRACTICES. WASH AND DRY HANDS.

FULL CONTACT

MATERIAL: NITRILE RUBBER

MINIMUM LAYER THICKNESS: 0.4 MM

BREAK THROUGH TIME: 480 MIN

MATERIAL TESTED: CAMATRIL® (KCL 730, SIZE M)

SPLASH CONTACT

MATERIAL: CHLOROPRENE

MINIMUM LAYER THICKNESS: 0.65 MM

BREAK THROUGH TIME: 120 MIN

MATERIAL TESTED: KCL 720 CAMAPREN

IF USED IN SOLUTION, OR MIXED WITH OTHER SUBSTANCES, AND UNDER CONDITIONS WHICH DIFFER FROM EN 374, CONTACT THE SUPPLIER OF THE CE APPROVED GLOVES. THIS RECOMMENDATION IS ADVISORY ONLY AND MUST BE EVALUATED BY AN INDUSTRIAL HYGIENIST AND SAFETY OFFICER FAMILIAR WITH THE SPECIFIC SITUATION OF ANTICIPATED USE BY OUR CUSTOMERS. IT SHOULD NOT BE CONSTRUED AS OFFERING AN APPROVAL FOR ANY SPECIFIC USE SCENARIO.

BODY PROTECTION

COMPLETE SUIT PROTECTING AGAINST CHEMICALS, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

RESPIRATORY PROTECTION

WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE APPROPRIATE USE A FULL-FACE RESPIRATOR WITH MULTIPURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

CONTROL OF ENVIRONMENTAL EXPOSURE

DO NOT LET PRODUCT ENTER DRAINS. RISK OF EXPLOSION.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	COLORLESS LIQUID
ODOUR	ETHANOLIC
ODOUR THRESHOLD	0.004 PPM
PH	7 AT 70 G/L AT 20 °C
MELTING	-90 °C (Lit.)
POINT/FREEZING POINT	
INITIAL BOILING POINT	116 - 118 °C (Lit.)
AND BOILING RANGE	
FLASH POINT	NO DATA AVAILABLE
EVAPORATION RATE	NO DATA AVAILABLE
FLAMMABILITY (SOLID, GAS)	NO DATA AVAILABLE
UPPER/LOWER	UPPER EXPLOSION LIMIT: 11.2 %(V)
FLAMMABILITY OR	LOWER EXPLOSION LIMIT: 1.4 %(V)
EXPLOSIVE LIMITS	
VAPOUR PRESSURE	< 10 HPA AT 20 °C
VAPOUR DENSITY	2.56 AT 20 °C - (AIR = 1.0)
RELATIVE DENSITY	0.81 g/L (Lit.)
WATER SOLUBILITY	66 G/L AT 20 °C
PARTITION	LOG POW: 1 AT 25 °C - BIOACCUMULATION IS NOT
COEFFICIENT: N-	EXPECTED.
OCTANOL/WATER	
AUTO-IGNITION	NO DATA AVAILABLE
TEMPERATURE	
DECOMPOSITION	NO DATA AVAILABLE
TEMPERATURE	
VISCOSITY	NO DATA AVAILABLE
EXPLOSIVE	NO DATA AVAILABLE
PROPERTIES	
OXIDIZING PROPERTIES	NONE

OTHER SAFETY INFORMATION

SURFACE TENSION	69.9 MN/M AT 1G/L AT 20 °C
RELATIVE VAPOUR	2.56 AT 20 °C - (AIR = 1.0)
DENSITY	

SECTION 10. STABILITY AND REACTIVITY

REACTIVITY	VAPOR/AIR-MIXTURES ARE EXPLOSIVE AT INTENSE WARMING.
CHEMICAL STABILITY	THE PRODUCT IS CHEMICALLY STABLE UNDER STANDARD AMBIENT CONDITIONS (ROOM TEMPERATURE).

POSSIBILITY OF HAZARDOUS REACTIONS	RISK OF IGNITION OR FORMATION OF INFLAMMABLE GASES OR VAPOURS WITH: STRONG OXIDISING AGENTS CHROMIUM(VI) OXIDE EXOTHERMIC REACTION WITH: ALKALI METALS ALKALINE EARTH METALS ALUMINUM STRONG REDUCING AGENTS ACID CHLORIDES
CONDITIONS TO AVOID	EXPOSURE TO MOISTURE. HEATING.
INCOMPATIBLE MATERIALS	RUBBER, VARIOUS PLASTICS
HAZARDOUS DECOMPOSITION PRODUCTS	IN THE EVENT OF FIRE: SEE SECTION 5

SECTION 11. TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY	LD50 ORAL - RAT - 790 MG/KG REMARKS: LIVER: FATTY LIVER DEGENERATION. KIDNEY, URETER, BLADDER: OTHER CHANGES. BLOOD: OTHER CHANGES. (RTECS) INHALATION: NO DATA AVAILABLE LD50 DERMAL - RABBIT - MALE - 3,430 MG/KG (OECD TEST GUIDELINE 402) NO DATA AVAILABLE
SKIN CORROSION/IRRITATION	SKIN - RABBIT RESULT: SKIN IRRITATION - 2 H REMARKS: (ECHA) (REGULATION (EC) NO 1272/2008, ANNEX VI)
SERIOUS EYE DAMAGE/EYE IRRITATION	EYES – RABBIT RESULT: IRREVERSIBLE EFFECTS ON THE EYE (OECD TEST GUIDELINE 405) REMARKS: (REGULATION (EC) NO 1272/2008, ANNEX VI)
RESPIRATORY OR SKIN SENSITISATION	NO DATA AVAILABLE

**GERM CELL
MUTAGENICITY**

TEST TYPE: MUTAGENICITY (MAMMAL CELL TEST):
MICRONUCLEUS.

TEST SYSTEM: CHINESE HAMSTER LUNG CELLS
METABOLIC ACTIVATION: WITHOUT METABOLIC
ACTIVATION

RESULT: NEGATIVE

REMARKS: (ECHA)

TEST TYPE: IN VITRO MAMMALIAN CELL GENE
MUTATION TEST

TEST SYSTEM: CHINESE HAMSTER LUNG CELLS
METABOLIC ACTIVATION: WITH AND WITHOUT
METABOLIC ACTIVATION

METHOD: OECD TEST GUIDELINE 476

RESULT: NEGATIVE

TEST TYPE: MICRONUCLEUS TEST

SPECIES: MOUSE

APPLICATION ROUTE: ORAL

METHOD: OECD TEST GUIDELINE 474

RESULT: NEGATIVE

CARCINOGENICITY

IARC:

NO INGREDIENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS PROBABLE, POSSIBLE OR CONFIRMED
HUMAN CARCINOGEN BY IARC.

NTP:

NO INGREDIENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS
IDENTIFIED AS A KNOWN OR ANTICIPATED
CARCINOGEN BY NTP.

OSHA:

NO COMPONENT OF THIS PRODUCT PRESENT AT
LEVELS GREATER THAN OR EQUAL TO 0.1% IS ON
OSHA'S LIST OF REGULATED CARCINOGENS.

**REPRODUCTIVE
TOXICITY**

NO DATA AVAILABLE

**SPECIFIC TARGET
ORGAN TOXICITY -
SINGLE EXPOSURE**

MAY CAUSE RESPIRATORY IRRITATION.
MAY CAUSE DROWSINESS OR DIZZINESS.

**SPECIFIC TARGET
ORGAN TOXICITY -
REPEATED EXPOSURE**

NO DATA AVAILABLE

ASPIRATION HAZARD

NO DATA AVAILABLE

**ADDITIONAL
INFORMATION**

RTECS: EO1400000

CENTRAL NERVOUS SYSTEM DEPRESSION,
GASTROINTESTINAL DISTURBANCE, DRYING,
CRACKING OF THE SKIN, SKIN IRRITATION.

DRYING, CRACKING OF THE SKIN, SKIN IRRITATION

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL,
PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE
NOT BEEN THOROUGHLY INVESTIGATED.

STOMACH - IRREGULARITIES - BASED ON HUMAN
EVIDENCE

SECTION 12. ECOLOGICAL INFORMATION

TOXICITY

TOXICITY TO FISH

STATIC TEST LC50 - PIMEPHALES PROMELAS
(FATHEAD MINNOW) - 1,376 MG/L - 96 H

TOXICITY TO DAPHNIA
AND OTHER AQUATIC
INVERTEBRATES

STATIC TEST EC50 - DAPHNIA MAGNA (WATER FLEA) -
1,328 MG/L - 48 H

TOXICITY TO ALGAE

STATIC TEST ERC50 - PSEUDOKIRCHNERIELLA
SUBCAPITATA (GREEN ALGAE) - 225 MG/L - 96 H

TOXICITY TO BACTERIA

STATIC TEST EC50 - PSEUDOMONAS PUTIDA - 4,390
MG/L - 17 H

TOXICITY TO DAPHNIA
AND OTHER AQUATIC
INVERTEBRATES(CHRONIC
TOXICITY)

SEMI-STATIC TEST EC50 - DAPHNIA MAGNA (WATER
FLEA) - 18 MG/L - 21 D

PERSISTENCE AND DEGRADABILITY

BIODEGRADABILITY

AEROBIC - EXPOSURE TIME 20 D
RESULT: 92 % - READILY BIODEGRADABLE.
REMARKS: (ECHA)

RATIO BOD/THBOD

33 %
REMARKS: (IUCLID)

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION

ONCORHYNCHUS MYKISS (RAINBOW TROUT) - 24 H -
921 MG/L(N-BUTANOL)

BIOCONCENTRATION FACTOR (BCF): 0.38

MOBILITY IN SOIL	NO DATA AVAILABLE
RESULTS OF PBT AND VPVB ASSESSMENT	PBT/VPVB ASSESSMENT NOT AVAILABLE AS CHEMICAL SAFETY ASSESSMENT NOT REQUIRED/NOT CONDUCTED
OTHER ADVERSE EFFECTS	NO DATA AVAILABLE

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

PRODUCT	WASTE MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH THE NATIONAL AND LOCAL REGULATIONS. LEAVE CHEMICALS IN ORIGINAL CONTAINERS. NO MIXING WITH OTHER WASTE. HANDLE UNCLEANED CONTAINERS LIKE THE PRODUCT ITSELF.
CONTAMINATED PACKAGING	DISPOSE OF AS UNUSED PRODUCT.

SECTION 14. TRANSPORT INFORMATION

DOT (US)

PROPER SHIPPING NAME:	BUTANOLS
UN NUMBER:	1120
CLASS:	3
PACKING GROUP:	III
REPORTABLE QUANTITY (RQ):	5000 LBS
POISON INHALATION HAZARD:	NO

IMDG

PROPER SHIPPING NAME:	BUTANOLS
UN NUMBER:	1120
CLASS:	3
PACKING GROUP:	III
EMS-NO:	F-E, S-D

IATA

PROPER SHIPPING NAME:	BUTANOLS
UN NUMBER:	1120
CLASS:	3
PACKING GROUP:	III

SECTION 15. REGULATORY INFORMATION

CERCLA REPORTABLE QUANTITY

COMPONENTS	CAS-NO.	COMPONENT RQ (LBS)	CALCULATED PRODUCT RQ (LBS)
N-BUTANOL	71-36-3	5000	5000
N-BUTANOL	71-36-3	100	100 (F003)

SARA 304 EXTREMELY HAZARDOUS SUBSTANCES REPORTABLE QUANTITY

THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 304 EHS RQ.

SARA 302 EXTREMELY HAZARDOUS SUBSTANCES THRESHOLD PLANNING QUANTITY

THIS MATERIAL DOES NOT CONTAIN ANY COMPONENTS WITH A SECTION 302 EHS TPQ.

SARA 311/312 HAZARDS FIRE HAZARD
 ACUTE HEALTH HAZARD
 CHRONIC HEALTH HAZARD

SARA 313 THE FOLLOWING COMPONENTS ARE SUBJECT TO
REPORTING LEVELS ESTABLISHED BY SARA TITLE III,
SECTION 313:

	CAS-NO.	CONCENTRATION
N-BUTANOL	71-36-3	≥ 90 - ≤ 100%

US STATE REGULATIONS**MASSACHUSETTS RIGHT TO KNOW**

N-BUTANOL 71-36-3

PENNSYLVANIA RIGHT TO KNOW

N-BUTANOL 71-36-3

MAINE CHEMICALS OF HIGH CONCERN

PRODUCT DOES NOT CONTAIN ANY LISTED CHEMICALS

VERMONT CHEMICALS OF HIGH CONCERN

PRODUCT DOES NOT CONTAIN ANY LISTED CHEMICALS

WASHINGTON CHEMICALS OF HIGH CONCERN

PRODUCT DOES NOT CONTAIN ANY LISTED CHEMICALS

THE INGREDIENTS OF THIS PRODUCT ARE REPORTED IN THE FOLLOWING INVENTORIES:

TSCA ALL SUBSTANCES LISTED AS ACTIVE ON THE TSCA
INVENTORY

TSCA LIST

NO SUBSTANCES ARE SUBJECT TO A SIGNIFICANT NEW USE RULE.
NO SUBSTANCES ARE SUBJECT TO TSCA 12(B) EXPORT NOTIFICATION
REQUIREMENTS.

SECTION 16. OTHER INFORMATION

FULL TEXT OF H-STATEMENTS REFERRED TO UNDER SECTIONS 2 AND 3.

H226	FLAMMABLE LIQUID AND VAPOUR.
H302	HARMFUL IF SWALLOWED.
H315	CAUSES SKIN IRRITATION.
H318	CAUSES SERIOUS EYE DAMAGE.
H335	MAY CAUSE RESPIRATORY IRRITATION.
H336	MAY CAUSE DROWSINESS OR DIZZINESS.

MSDS LEGEND

MW:	MOLECULAR WEIGHT
MF:	MOLECULAR FORMULA
VOC:	VOLATILE ORGANIC COMPOUNDS
ACGIH:	AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGINISTS
CAS:	CHEMICAL ABSTRACTS SERIVE REGISTRY NUMBER
OSHA:	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PEL:	PERMISSIBLE EXPOSURE LIMIT (OSHA)
TLV:	THRESHOLD LIMIT VALUE (ACGIH)

IMPORTANT:

THE INFORMATION ABOVE IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST INFORMATION CURRENTLY AVAILABLE TO US. HOWEVER, WE MAKE NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, AND WE ASSUME NO LIABILITY RESULTING FROM ITS USE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION FOR THEIR PARTICULAR PURPOSES. IN NO EVENT SHALL CII BE LIABLE FOR ANY CLAIMS, LOSSES, OR DAMAGES OF ANY THIRD PARTY OR FOR LOST PROFITS OR ANY SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES, HOWSOEVER ARISING, EVEN IF CII HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

VERSION: 3.2

REVISION DATE: 02/10/2025